



Colour

Detailed Specifications



CopyCentre C32 Colour.



CopyCentre C40 Colour shown with Duplex Automatic Document Feeder and Optional Two-Tray Module.

	CopyCentre™ C32 Colour Digital Copier		CopyCentre™ C40 Colour Digital Copier	
OUTPUT SPEED				
	Black and white	Colour	Black and white	Colour
	32 images per minute (ipm) A4	16 ipm A4	40 ipm A4	22 ipm A4
	20 ipm B4	11 ipm B4	24 ipm B4	13 ipm B4
	17 ipm A3	9 ipm A3	20 ipm A3	11 ipm A3
	CopyCentre™ C32 Colour/C40 Colour			

COPYING	
<i>Document Scanner</i>	Duplex Automatic Document Feeder with 50-sheet capacity
<i>Sides (input:output)</i>	1:1, 1:2, 2:2 and 2:1
<i>Quantity</i>	1 to 9,999
<i>Resolution</i>	600 x 600 dpi
<i>Concurrency</i>	Concurrent scanning and copying
<i>Digital Imaging</i>	AutoIQ automatic digital image quality control Auto rotation 180° or 270° when needed Image shift Edge erase Auto centring Original type selection (photo/text, photo, text, map, inkjet, highlighted) Lighter/darker Background suppression Contrast Sharpness Screening Negative image Mirror image

Continued





CopyCentre™ C32/C40 Colour Digital Copiers

COPYING *Continued*

Copy Pre-collation Memory	256 MB RAM plus 18 GB hard disk drive
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up – up to six columns by six rows Transparency dividers Covers insertion (front only, front and back, back only; blank or printed) Build Job (produce multiple sets from stored job segments) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Context-sensitive help screens Negative image Mirror image
Foreign Device Interface (optional)	Interface to third-party access control devices, coin machines and card readers
USB Port	PC interface for upload/download of internal auditor data
PAPER HANDLING – Duplex Automatic Document Feeder	
Capacity*	50 sheets
Speed	32 ipm A4 long edge feed (LEF)
Paper Sizes Sensed	A5 long edge feed (LEF) or short edge feed (SEF) A4 LEF or SEF B4 SEF A3 SEF B5 SEF
Weights	60 to 120 gsm

*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.



CopyCentre™ C32/C40 Colour Digital Copiers

PAPER HANDLING – Bypass Tray

Capacity*	100 sheets
Sizes	A6 to SRA3
Weights	60 to 220 gsm
Types	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined) Lightweight Heavyweight Envelopes

PAPER HANDLING – Front-Loading Paper Tray (standard)

Tray 1	520 sheets
Sizes	User adjustable from A5 to A3
Weights	64 to 105 gsm
Types	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined)

PAPER HANDLING – INPUT TRAY OPTIONS – One Tray with Stand Option

Tray 2	520 sheets
Sizes	User adjustable from A5 to A3
Weights	64 to 105 gsm
Types	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
Total Capacity	1,140 sheets (Includes Tray 1, Tray 2 and Bypass Tray)

*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.



Colour

CopyCentre™ C32/C40 Colour Digital Copiers

PAPER HANDLING – INPUT TRAY OPTIONS – Three Tray Option (Tray One and Two plus Two-Tray Module)

Tray 2 – Tray 4	520 sheets
Sizes	User adjustable from A5 to A3
Weights	64 to 105 gsm
Types	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
Total Capacity	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

PAPER HANDLING – INPUT TRAY OPTIONS – High-Capacity Feeder Option (Tray One and Two plus High-Capacity Feeder)

Tray 2	520 sheets
Sizes	User adjustable from A5 to A3
Tray 3 and Tray 4	2,000 sheets
Sizes	B5, A4
Weights	64 to 105 gsm
Types	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
Total Capacity	3,140 sheets (Includes Tray 1, Tray 2, High-Capacity Feeder and Bypass Tray)

PAPER HANDLING – Convenience Stapler Option

Capacity*	Up to 50 sheets (5,000 staples per cartridge)
------------------	---

OUTPUT OPTIONS – Center Tray

Stacking Tray	400 sheets (200 sheets with finisher option)
Sizes	A6 to SRA3

OUTPUT – Office Finisher (optional)

Stacking Tray	1,000 sheets
Sizes	B5 to A3
Weights	60 to 105 gsm
Stapling	Single (any corner) and dual Auto stapling (50 sheets maximum) A3, A4, B4 and B5 sizes supported

*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.



Colour

CopyCentre™ C32/C40 Colour Digital Copiers

ACCOUNTING

Internal Auditron Tracks and limits black and colour copy usage; supports up to 2,000 user accounts or 300 general accounts
Auditron report printout

Note: Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software.

CopyCentre™ C32 Colour/C40 Colour

BASIC CONFIGURATIONS*

Digital Copier with Duplex Automatic Document Feeder, two paper trays, stand and centre output tray

ACCESSORY OPTIONS

Office Finisher (50-sheet stapling)
Foreign Device Interface
Image Overwrite Security
Convenience Stapler

ELECTRICAL REQUIREMENTS

220-240 V Nominal, 50 Hz, 10A

	CopyCentre™ C32 Colour	CopyCentre™ C40 Colour
POWER CONSUMPTION		
Running	< 540 watts	< 540 watts
Standby	< 192 watts	< 192 watts
Low-Power Mode	< 128 watts	< 159 watts
Sleep Mode	< 15 watts	< 15 watts
Warm-up	3 minutes (maximum)	3 minutes (maximum)
Low-Power Recovery	30 seconds (maximum)	30 seconds (maximum)

*Features, configurations and options may vary by location.



CopyCentre™ C32/C40 Colour Digital Copiers

ENVIRONMENTAL CONSIDERATIONS

Required Temperature Range 10° to 32° C

Required Relative Humidity 10% to 85%

Heat Emission 1,844 BTU/Hr running
656 BTU/Hr standby

Noise Emission 34.8 dB(A) standby
51.9 dB(A) running
55.5 dB(A) impulse

DIMENSIONS AND WEIGHT

	<i>Width</i>	<i>Depth</i>	<i>Height</i>	<i>Weight</i>
Fully Configured	1,346 mm	636 mm	1,116 mm	274 kg

SPACE REQUIREMENTS

	<i>Width</i>	<i>Depth</i>	<i>Height</i>
Basic Configuration Without Finisher	1,461 mm	1,755 mm	1,600 mm
Basic Configuration With Finisher	1,908 mm	1,755 mm	1,600 mm

CERTIFICATIONS

89/336/EEC
UL Listed (UL 1950, Third Edition)
CB Certified (IEC 60950/EN 60950)
73/23/EEC
WHQL
Novell® NetWare®



Colour

United Kingdom
Tel: 0870 241 3245

Eire
Tel: 0818 300015

CopyCentre™ C32/C40 Colour Digital Copiers

SUPPLIES

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>
Black Toner	6R1122	1
Cyan Toner	6R1123	1
Magenta Toner	6R1124	1
Yellow Toner	6R1125	1
Drum Cartridge	13R579	1
Fuser Cartridge	8R12905	1
Waste Toner Container	8R12903	1
Staples (5,000 per cartridge)	8R7644	4



XEROX
Worldwide Partner

© 2003 XEROX CORPORATION. All rights reserved. XEROX®, The Document Company®, the digital X® CopyCentre™ and Copier Assistant are trademarks of XEROX CORPORATION. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. Other marks are trademarks or registered trademarks of the companies with which they are associated. Whilst this information is correct at the time of going to press, Xerox Europe reserves the right to change specifications of the equipment described herein without notice.

09/03

C32FS-01EB