

### Detailed Specifications



*CopyCentre C65 shown with Offsetting Catch Tray and Bypass Tray.*



*CopyCentre C75 shown with optional 5,100-sheet High-Capacity Feeder and Advanced Office Finisher.*



*CopyCentre C90 shown with optional Professional Finisher.*

|   | CopyCentre® C65 Digital Copier                                   | CopyCentre® C75 Digital Copier                                   | CopyCentre® C90 Digital Copier |
|---|--|--|--------------------------------|
| <b>OUTPUT SPEED</b>   |  |  |                                |
| 65 images per minute (ipm) letter<br>(8.5 x 11"/216 x 279 mm/A4)          | 75 images per minute (ipm) letter<br>(8.5 x 11"/216 x 279 mm/A4) | 90 images per minute (ipm) letter<br>(8.5 x 11"/216 x 279 mm/A4) |                                |
| 32 ipm legal<br>(8.5 x 14"/216 x 356 mm)                                  | 37 ipm legal<br>(8.5 x 14"/216 x 356 mm)                         | 45 ipm legal<br>(8.5 x 14"/216 x 356 mm)                         |                                |
| 32 ipm ledger<br>(11 x 17"/279 x 432 mm/A3)                               | 37 ipm ledger<br>(11 x 17"/279 x 432 mm/A3)                      | 45 ipm ledger<br>(11 x 17"/279 x 432 mm/A3)                      |                                |
| <b>FIRST-IMAGE-OUT TIME—letter size, from platen to finisher top tray</b> |  |  |                                |
| 6.8 seconds   | 6.8 seconds  | 6.0 seconds  |                                |

### CopyCentre® C65/C75/C90

|                             |   |
|-----------------------------|---|
| <b>COPYING</b>              |   |
| <b>Document Scanner</b>     | Duplex Automatic Document Feeder with 100-sheet capacity  |
| <b>Sides (input:output)</b> | 1:1, 1:2, 2:2 and 2:1   |
| <b>Quantity</b>             | 1 to 9,999  |
| <b>Resolution</b>           | 600 x 600 dpi x 8 bit   |
| <b>Concurrency</b>          | Concurrent scanning and copying   |
| <b>Digital Imaging</b>      | AutoIQ automatic digital image quality control<br>Auto rotation 90° or 270° when needed<br>Image shift<br>Edge erase<br>Edge-to-edge copying<br>Auto centering<br>Original type selection (normal, text, halftone, photo)<br>Lighter/darker<br>Background suppression<br>Contrast<br>Sharpness<br>Screening |

*Continued*

## CopyCentre® C65/C75/C90 Digital Copiers

COPYING *Continued*

|  |   |
|--|---|
| <b>Copy Pre-collation Memory</b>                           | 64 MB RAM standard expandable to 192 MB<br>9.1 GB disk storage (minimum)  |
| <b>Reduction/Enlargement</b>                               | Variable zoom from 25% to 400% in 1% increments<br>Anamorphic zoom<br>Six user-programmable percentages   |
| <b>Special Features</b>                                    | Annotation (user-editable comment, pagination, bates stamping, and date stamping)<br>Auto paper select<br>Auto reduction/enlargement to fit selected paper size<br>Auto registration<br>Auto tray switching<br>Automatic job recovery<br>Booklet creation<br>N-up—up to six columns by six rows<br>Transparency dividers (blank or printed)<br>Negative image<br>Mirror image<br>Covers insertion (front only, front and back, back only; blank or printed)<br>Build Job (enables special programming for different pages in one document—can be used for inserts, tabs, different paper sources, and mixing input from the document glass and the document feeder)<br>Store and recall job programming<br>Job interrupt<br>Bound document copying<br>Sample set<br>Mixed-size originals<br>Folding (requires Professional Finisher)<br>Saddle-stitch booklets (requires Professional Finisher)<br>Context-sensitive help screens |
| <b>Foreign Device Interface<br/>RS-232 Port (optional)</b> | Interface to third-party access control devices, coin machines, card readers<br>Supports a variety of vending stations available through the Xerox Custom Application Service<br>PC interface for upload/download of internal auditron data   |
| <b>Accessibility Option</b>                                | Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the RS-232 port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.*   |

\*Available in US only.

## CopyCentre® C65/C75/C90 Digital Copiers

## PAPER HANDLING—Duplex Automatic Document Feeder (DADF)

|                           |   |
|---------------------------|---|
| <b>Capacity*</b>          | 100 sheets  |
| <b>Speed</b>              | 65 images per minute—letter/8.5 x 11"/216 x 279 mm/A4 long edge feed (LEF)  |
| <b>Paper Sizes Sensed</b> | Statement/5.5 x 8.5"/140 x 216 mm/A5 LEF or short edge feed (SEF)<br>Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF<br>Legal/8.5 x 14"/216 x 356 mm SEF<br>Ledger/11 x 17"/279 x 432 mm/A3 SEF |
| <b>Weights</b>            | 16 lb to 32 lb/60 to 120 gsm  |

## PAPER HANDLING—Front-Loading Paper Trays

|                  |   |
|------------------|---|
| <b>Number</b>    | Four  |
| <b>Capacity*</b> | 500 sheets each   |
| <b>Sizes</b>     | User adjustable from statement/5.5 x 8.5"/140 x 216 mm/A5 to ledger/11 x 17"/279 x 432 mm/A3<br>Service adjustable for 12 x 18"/305 x 457 mm      |
| <b>Weights</b>   | 16 lb bond to 110 lb index/60 to 200 gsm  |
| <b>Types</b>     | Letterhead<br>Preprinted forms<br>Labels<br>Transparencies<br>Hole-punched<br>Recycled paper<br>Bond<br>Index<br>Cover<br>Tab stock<br>Card stock |

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.

## CopyCentre® C65/C75/C90 Digital Copiers

## PAPER HANDLING—Bypass Tray

|                  |   |
|------------------|---|
| <b>Capacity*</b> | 50 sheets   |
| <b>Sizes</b>     | 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm  |
| <b>Weights</b>   | 16 lb bond to 110 lb index/60 to 200 gsm  |
| <b>Types</b>     | Letterhead<br>Preprinted forms<br>Labels<br>Transparencies<br>Hole-punched<br>Recycled paper<br>Bond<br>Index<br>Cover<br>Tab stock<br>Card stock |

## PAPER HANDLING—3,100-sheet High-Capacity Feeder (HCF) (C65 optional, C75 standard)

|                        |  |
|------------------------|--|
| <b>Capacity*</b>       | 3,100 sheets   |
| <b>Paper Size</b>      | Letter/8.5 x 11"/216 x 279 mm/A4 LEF   |
| <b>Weights</b>         | 16 lb to 32 lb bond /60 to 120 gsm   |
| <b>Total Capacity*</b> | 5,150 sheets (with Bypass Tray, four Front-Loading Paper Trays and High-Capacity Feeder) |

## PAPER HANDLING—5,100-sheet High-Capacity Feeder (HCF) (C75 optional, C90 standard)

|                        |  |
|------------------------|--|
| <b>Capacity*</b>       | 5,100 sheets   |
| <b>Paper Size</b>      | Letter/8.5 x 11"/216 x 279 mm/A4 LEF   |
| <b>Weights</b>         | 16 lb to 32 lb bond/60 to 120 gsm  |
| <b>Total Capacity*</b> | 7,150 sheets (with Bypass Tray, four Front-Loading Paper Trays and High-Capacity Feeder) |

## PAPER HANDLING—11 x 17" Large Capacity Kit (optional with 5,100-sheet HCF)

|                                 |   |
|---------------------------------|---|
| <b>Capacity* and Paper Size</b> | 5,100 sheets Letter/8.5 x 11"/216 x 279 mm/A4 LEF<br>2,500 sheets Ledger/11 x 17"/279 x 432 mm/A3 SEF |
| <b>Weights</b>                  | 16 lb to 32 lb bond/60 to 120 gsm   |

## PAPER HANDLING—Convenience Stapler and Work Surface (optional)

|                  |  |
|------------------|--|
| <b>Capacity*</b> | Up to 50 sheets<br>5,000 staples per cartridge |
|------------------|--|

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.

## CopyCentre® C65/C75/C90 Digital Copiers

## OUTPUT OPTIONS—Finishers

|  |  |
|--|--|
| <b>Offsetting Catch Tray<br/>(C65 only)</b>              | Capacity:* 250 sheets<br>Paper sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm   |
| <b>Office Finisher<br/>(50-sheet stapling)</b>           | <p><b>Top Tray</b><br/>Capacity:* 250 sheets<br/>Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm</p> <p><b>Main Tray</b><br/>Capacity:* 2,000 sheets<br/>Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm<br/>Weights: 16 lb bond to 110 lb index/60 to 200 gsm<br/>Stapling Positions: Single and dual, portrait and landscape orientations<br/>Maximum Stapler Capacity:* 50 sheets</p>   |
| <b>Advanced Office Finisher<br/>(100-sheet stapling)</b> | <p><b>Top Tray</b><br/>Capacity:* 250 sheets<br/>Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm</p> <p><b>Main Tray</b><br/>Capacity:* 2,000 sheets<br/>Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm<br/>Weights: 16 lb bond to 110 lb index/60 to 200 gsm<br/>Stapling Positions: Single and dual, portrait and landscape orientations<br/>Maximum Stapler Capacity:* 100 sheets for legal/8.5 x 14"/216 x 356 mm and below; 50 sheets for larger sizes</p>   |
| <b>Professional Finisher</b>                             | <p><b>Top Tray</b><br/>Capacity:* 250 sheets<br/>Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm</p> <p><b>Main Tray</b><br/>Capacity:* 2,000 sheets<br/>Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm<br/>Weights: 16 lb bond to 110 lb index/60 to 200 gsm<br/>Stapling Positions: Single and dual, portrait and landscape orientations<br/>Maximum Stapler Capacity:* 100 sheets for legal/8.5 x 14"/216 x 356 mm and below; 50 sheets for larger sizes</p> <p><b>Booklet Maker</b><br/>Capacity:* Tray stop up, 30 booklets (one to five sheets per booklet); tray stop down, unlimited<br/>Paper Sizes: 8.5 x 11"/216 x 279 mm/A4, 8.5 x 14"/216 x 356 mm, 11 x 17"/279 x 432 mm/A3<br/>Weights: 16 lb bond to 100 lb index/60 to 200 gsm<br/>Saddle-Stitch Capacity:* 2 to 15 sheets (8- to 60-page booklet)<br/>V-Fold Capacity:* One to five sheets (unstapled)</p> <p><b>Tri-Folder</b><br/>Capacity:* Tray stop up, 55 sheets; tray stop down, unlimited<br/>Paper Sizes: 8.5 x 11"/216 x 279 mm/A4<br/>Weights: 16 lb to 24 lb bond/60 to 90 gsm<br/>Folding: Single-sheet folds (simplex and duplex), C and Z shapes</p> |

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.

**CopyCentre® C65/C75/C90 Digital Copiers**

**ACCOUNTING**

**Internal Auditor**

Tracks copy use only; supports up to 2,500 user accounts (1 to 12 digits) or 11,000 general accounts (5 digits)  
Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software

**CopyCentre® C65**

**CopyCentre® C75**

**CopyCentre® C90**

**MONTHLY DUTY CYCLE**

Duty Cycle: Up to 250,000

Duty Cycle: Up to 300,000

Duty Cycle: Up to 400,000

**BASIC CONFIGURATIONS\***

Bypass Tray  
Offsetting Catch Tray

3,100-sheet High-Capacity Feeder  
Office Finisher

5,100-sheet High-Capacity Feeder  
Office Finisher

**CopyCentre® C65/C75/C90**

**ACCESSORY OPTIONS\***

- Office Finisher (50-sheet stapling)
- Advanced Office Finisher (100-sheet stapling)
- Professional Finisher (100-sheet stapling, saddle stitch booklet making, tri-fold)
- Convenience Stapler
- 3,100-sheet High-Capacity Feeder (C65 optional, C75 standard)
- 5,100-sheet High-Capacity Feeder (C75 optional, C90 standard)
- 11 x 17" Large Capacity Kit (optional with 5,100 sheet HCF)
- Image Overwrite Security
- Removable Hard Drive
- Foreign Device Interface/RS-232 Port
- Copy Pre-collation RAM Upgrade to 192 MB
- Xerox Copier Assistant™ Software (assistive software for the visually impaired or persons with limited dexterity or mobility)\*\*

**CopyCentre® C65**

**CopyCentre® C75**

**CopyCentre® C90**

**ELECTRICAL REQUIREMENTS**

Sole use of 115 volt, 20 ampere, 60 Hz circuit, NEMA 5-20R receptacle;  
100-sheet Stapling Finisher requires a separate 115 volt, 15 ampere,  
60 Hz circuit, NEMA 5-15R receptacle

Sole use of 120/240 volts (or)  
208Y/120-127 Volts, 3-Wire + PE  
(Protective Earth), 16 ampere,  
60Hz, NEMA 14-20R receptacle

\*Features, configurations and options may vary by location.  
\*\*Available in US only.

|                           | CopyCentre® C65 Digital Copier                 | CopyCentre® C75 Digital Copier                 | CopyCentre® C90 Digital Copier  |
|---------------------------|--|--|---|
| <b>POWER CONSUMPTION</b>  |  |  |   |
| <b>Running</b>            | < 1,425 watts with 50-sheet Stapling Finisher  | < 1,440 watts with 50-sheet Stapling Finisher  | < 1,870 watts with 50-sheet Stapling Finisher                           |
|                           | < 1,865 watts with 100-sheet Stapling Finisher | < 1,880 watts with 100-sheet Stapling Finisher | < 2,310 watts with 100-sheet Stapling Finisher or Professional Finisher |
| <b>Standby</b>            | < 450 watts                                    | < 360 watts                                    | < 341 watts   |
| <b>Low-Power Mode</b>     | < 255 watts                                    | < 339 watts                                    | < 280 watts   |
| <b>Sleep Mode</b>         | < 65 watts                                     | < 65 watts                                     | < 59 watts  |
| <b>Warm-up</b>            | Four minutes                                   | Four minutes                                   | Three minutes   |
| <b>Low-Power Recovery</b> | 30 seconds (maximum)                           | 30 seconds (maximum)                           | 30 seconds (maximum)  |

|                                     |  |  |  |
|-------------------------------------|--|--|--|
| <b>ENVIRONMENTAL CONSIDERATIONS</b> |  |  |  |
| <b>Required Temperature Range</b>   | 50° to 95° F/10° to 35° C                              | 50° to 95° F/10° to 35° C                              | 50° to 95° F/10° to 35° C                              |
| <b>Required Relative Humidity</b>   | 10% to 90%   | 10% to 90%   | 10% to 90%   |
| <b>Noise Emission</b>               | 39.9 dBA standby; 63.2 dBA operating; 73.3 dBA impulse | 39.4 dBA standby; 62.9 dBA operating; 69.0 dBA impulse | 38.5 dBA standby; 64.2 dBA operating; 70.0 dBA impulse |
| <b>Heat Emission</b>                | 1,540 BTU/hr standby; 4,870 BTU/hr operating           | 1,230 BTU/hr standby; 4,915 BTU/hr operating           | 1,165 BTU/hr standby; 6,386 BTU/hr operating           |
| <b>Ozone Emission</b>               | < 0.01 parts per million                               | < 0.01 parts per million                               | < 0.01 parts per million                               |

CopyCentre® C65/C75/C90

| <b>DIMENSIONS AND WEIGHT</b>   |              |              |                |                |
|--|--------------|--------------|----------------|----------------|
|  | <b>Width</b> | <b>Depth</b> | <b>Height</b>  | <b>Weight</b>  |
| <b>Fully Configured With 50-Sheet Stapling Office Finisher</b>           | 69"/1,753 mm | 28"/710 mm   | 44.8"/1,138 mm | 538 lbs/245 kg |
| <b>Fully Configured With 100-Sheet Stapling Advanced Office Finisher</b> | 80"/2,032 mm | 28"/710 mm   | 44.8"/1,138 mm | 609 lbs/278 kg |
| <b>Fully Configured With Professional Finisher</b>                       | 88"/2,235 mm | 28"/710 mm   | 44.8"/1,138 mm | 686 lbs/312 kg |

## CopyCentre® C65/C75/C90 Digital Copiers

## SPACE REQUIREMENTS\*

|  | <i>Width</i>  | <i>Depth</i> | <i>Height</i> |
|--|---------------|--------------|---------------|
| <i>Fully Configured With<br/>50-Sheet Stapling<br/>Office Finisher</i>           | 102"/2,591 mm | 69"/1,753 mm | 78"/1,981 mm  |
| <i>Fully Configured With<br/>100-Sheet Stapling<br/>Advanced Office Finisher</i> | 107"/2,718 mm | 69"/1,753 mm | 78"/1,981 mm  |
| <i>Fully Configured With<br/>Professional Finisher</i>                           | 109"/2,769 mm | 69"/1,753 mm | 78"/1,981 mm  |

## CERTIFICATIONS

FCC Class B Compliant (U.S.), DOC Class B Compliant (Canada)  
 89/336/EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950/EN 60950)  
 73/23/EEC (Europe)  
 95/5/EEC (Europe)

## SUPPLIES

| <i>Description</i>  | <i>Order Number</i> | <i>No. per Box</i> | <i>Expected Yield</i>  |
|---|---------------------|--------------------|--|
| Dry Ink Cartridge   | 6R1006              | 6                  | 23,500 (C65); 24,500 (C75);<br>28,000 (C90) per cartridge at<br>6% area coverage |
| Convenience Stapler<br>Staple Cartridge                       | 108R53              | 3                  | 5,000 staples per cartridge  |
| Staple Cartridge (for Office<br>[50-sheet stapling] Finisher) | 108R53              | 3                  | 5,000 staples per cartridge  |

Continued

\*No additional space required for 11 x 17" Large Capacity Kit or convenience stapler



CopyCentre® C65/C75/C90 Digital Copiers

SUPPLIES *Continued*

| <i>Description</i>   | <i>Order Number</i> | <i>No. per Box</i> | <i>Expected Yield</i>       |
|--|---------------------|--------------------|-----------------------------|
| Staple Housing Cartridge<br>(for Advanced Office [100-sheet stapling]<br>Finisher and Professional Finisher)<br><b>Note:</b> Staple Housing Cartridge comes filled with 5,000 staples. | 8R12912             | 1                  | N/A                         |
| Staples for Staple Housing Cartridge<br>(for Advanced Office [100-sheet stapling]<br>Finisher and Professional Finisher)   | 8R12898             | 3                  | 5,000 staples per cartridge |
| Professional Finisher<br>Booklet Maker Staples   | 8R12897             | 8                  | 2,000 staples per cartridge |

**Total satisfaction guaranteed.**

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox CopyCentre® which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



© 2003 XEROX CORPORATION. All rights reserved. XEROX®, CopyCentre® and Copier Assistant are trademarks of XEROX CORPORATION. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product appearance, build status and/or specifications are subject to change without notice. 3/04, 5/04, 02/05 C65FS-01UE C65FS-01UD 610P716210E