Technology Document Management Consulting Services

# **Detailed Specifications**



WorkCentre Pro 65 shown with optional 3,100-sheet High-Capacity Feeder and Office Finisher.



WorkCentre Pro 75 shown with optional 5,100-sheet High-Capacity Feeder and Advanced Office Finisher.



WorkCentre Pro 90 shown with optional Professional Finisher.

	WorkCentre® Pro 65 Advanced Multifunction System	WorkCentre® Pro 75 Advanced Multifunction System	WorkCentre® Pro 90 Advanced Multifunction System		
OUTPUT SPEED—printing and copying					
	65 images per minute (ipm) letter (8.5 x 11"/216 x 279 mm/A4)	75 images per minute (ipm) letter (8.5 x 11"/216 x 279 mm/A4)	90 images per minute (ipm) letter (8.5 x 11"/216 x 279 mm/A4)		
	32 ipm legal (8.5 x 14"/216 x 356 mm)	37 ipm legal (8.5 x 14"/216 x 356 mm)	45 ipm legal (8.5 x 14"/216 x 356 mm)		
	32 ipm ledger (11 x 17"/279 x 432 mm/A3)	37 ipm ledger (11 x 17"/279 x 432 mm/A3)	45 ipm ledger (11 x 17"/279 x 432 mm/A3)		
FIRST-IMAGE-OUT TIME—letter size, from platen to finisher top tray					
	6.8 seconds	6.8 seconds	6.0 seconds		
		WorkCentre® Pro 65/75/90			

	WorkCentre® Pro 65/75/90
NETWORK PRINTING—S	Mart <sup>™</sup> Network Controller
Processor	Intel® Celeron® 433 MHz
Memory	128 MB RAM (256 MB max)
System Disk	Minimum 9.1 GB
Printer Languages (auto sensing/ switching)	PostScript® 3 emulation TIFF PCL® 6 (PCL 5e) emulation PDF LCDS, SCS, XES and IPDS through third-party transforms

## **NETWORK PRINTING**—resolution, printing via CentreWare® software

PostScript emulation: 600 x 600 dpi for 256 levels of gray: 1200 x 1200 dpi and 1800 x 1800 dpi for 256 levels

of gray via patented emulation process.

PCL emulation: 600 x 600 dpi

## WorkCentre® Pro 65/75/90 Advanced Multifunction Systems

## **NETWORK PRINTING—printing features\***

Edge-to-edge printing

Secure print

Delay print (specific time)

Sample set Booklet creation Cover selection

Paper selection by attribute

N-up

Saddle-stitch booklet making (requires Professional Finisher)

Folding (requires Professional Finisher)

Watermark

Fit to new paper size
Transparency interleave
Banner sheet enable/disable
Output tray selection
Image quality

Store and recall driver settings

#### PRINT PROTOCOLS AND NETWORKS

Physical Ethernet 100BaseT, 10Base2, 10Base5 via adapter

IEEE 1284 parallel (compatibility mode)

Wireless Ethernet (IEEE 802.11b) via third-party adapters

USB printer port (optional)

*Operating Systems* Microsoft Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®, Windows Server 2003

Novell® NetWare® 4.x, 5.x, 6 Mac OS® 8.x, 9.x, OS X Solaris® 2.5.1, 2.6 and higher

HP-UX® 10.2, 11.x IBM AIX® 4.2 and higher

Linux® Intel®
—Red Hat®
—Caldera®

—Mandrake<sup>™</sup> (LPRNG printing infrastructure)

—Corel® (i386) —TurboLinux® (i386) —SuSE® (i386) Linux Power PC®

—TurboLinux Server 6.0.2

Network Protocols TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP

NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)

AppleTalk®: EtherTalk®

Microsoft Windows Networking over IP and NetBEUI

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems				
PRINT PROTOCOLS AND NE	TWORKS Continued				
Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® ∨2, HTTP, RARP, DHCP Autonet				
Fonts	PostScript 3: 136 PostScript standard fonts PCL: 80 scalable fonts, line printer and bitmap format line printer fonts Font Management Utility for downloading additional fonts				
Print Drivers	Environment	PCL5e		PCL 6	PostScript
_	Windows 95/98/Me	Bidirectional enh	anced*	Bidirectional enhanced*	Bidirectional enhanced*
	Windows 2000/XP, Windows Server 2003 (Microsoft certified)	Bidirectional with user-selectable in (standard and er	nterface	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Windows NT 4.0	Bidirectional with user-selectable in (standard** and	nterface	Bidirectional enhanced	Bidirectional with user-selectable interface (standard** and enhanced)
_	Macintosh® System 8.x, 9.x, OS X	N/A		N/A	Generic PPD
	Macintosh® System 9.x	N/A		N/A	Bidirectional via AppleTalk
Print Submission Tools	Environment		PCL		PostScript
	Solaris 2.5.1, 2.6 and higher; LF printing infrastructure; Linuand Linux Power PC	PRNG	Submission	Tool only	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Wi 95/98/Me/NT 4.0/2000/XP	ndows	Submission TIFF or PDF	Tool for any file	
CENTREWARE® INTERNET S	ERVICES—integrated device	Web page			
Device Status	Web server embedded on SMart network controller —Tray status/contents —Consumables status				
Print Queue Viewing	Complete job printing queue management—hold, release, promote and delete				
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection				
Device Administration	Allows simple, remote installation setting of configuration options and management of the device				
Browsers	Windows XP/2000/NT 4.0/Me/98/95: Netscape Navigator® 6.x, Microsoft Internet Explorer 5.x/6.x Macintosh 9.x/OS X: Netscape Navigator 6.x Linux: Netscape® 6.x				

<sup>\*</sup>Enhanced: Xerox custom graphical user interface.

\*\*Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems		
ETWORK SCANNING (optio	nal)		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan-to-network or fax jobs		
Input Speed	65 ipm—(letter/8.5 x 11"/216 x 279 mm/A4 long edge feed [LEF]) at all resolutions		
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi 100 x 200 dpi		
Maximum Scan Area	Ledger/11.7 x 17"/297 x 432 mm/A3		
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000) and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login		
Network Protocol	Novell (NCP via IPX/SPX) FTP via TCP/IP Microsoft SMB		
File Formats	TIFF 6.0 with G3 MH and G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression		
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on WorkCentre Pro user interface Variable data entered using virtual keyboard at WorkCentre Pro		
Scan Destinations	Scan to network server Scan to remote e-mail destinations via direct SMTP addresses Scan to e-mail via optional CentreWare® Scanning Services using MAPI 32-bit compliant e-mail client Scan to application (workflow, Electronic Document Management System) Scan to Microsoft Exchange public folders Scan to PC Desktop™ (Standard and Deluxe editions) Scan to Windows XP client via Windows Image Acquisition (WIA)		
Network Scanning With E-Mail Includes:	Template-based scanning (allows scan workflows to be easily created and replicated) Scan to network directory Scan to e-mail distribution Scan to Xerox or third-party applications Scan to Windows XP client (requires WIA driver downloadable from xerox.com)		
Scanning Software Options	Scan to PC Desktop Standard—includes everything in Network Scanning With E-mail, plus:  —Xerox CentreWare Scanning Services – software tools that enhance the administration and use of template-based scanning  —ScanSoft® PaperPort® SE 2.0 – image viewing and file management software  —ScanSoft OmniPage® SE 1.0 (for CW Distribution Server installation) and ScanSoft OmniPage SE 2.0 (for desktop/client installation) – OCR and file format conversion software  Scan to PC Desktop Deluxe—everything in Network Scanning With E-mail, plus:  —Xerox CentreWare Scanning Services – software tools that enhance the administration and use of template-based scanning  —ScanSoft PaperPort Pro 9.0 Office – image viewing and file management software  —ScanSoft OmniPage Pro 11.0 (for CW Distribution Server installation) and ScanSoft OmniPage Pro 12.0 Office (for desktop/client installation) – OCR and file format conversion software		

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems		
-MAIL (included with all n	network scanning options)		
Capability	Direct document e-mail from the device Manual address entry or directory (Exchange/Notes™/LDAP) address searching		
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi 100 x 200 dpi		
Maximum Scan Area	11.7 x 17"/297 x 432 mm/A3		
Network Protocol	SMTP, MIME encoded		
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000) and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login		
Directory Access	Supports corporate address list via LDAPv3 (Exchange/Notes)  Downloaded address list (comma-separated file format)		
File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression		
OPYING			
Document Scanner	Duplex Automatic Document Feeder with 100-sheet capacity		
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 9,999		
Resolution	600 x 600 dpi x 8 bit		
Concurrency	Concurrent scanning and printing		
Digital Imaging	Auto IQ automatic digital image quality control Auto rotation selection 90° or 270° when needed Image shift Edge erase Edge-to-edge copying Auto centering Original type selection (normal, text, halftone, photo) Lighter/darker Background suppression Contrast Sharpness Screening		

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems
<b>COPYING</b> Continued	
Copy Pre-collation Memory	64 MB RAM standard Optional upgrade to 192 MB 9.1 GB disk storage (minimum)
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Annotation (user-editable comment, pagination, bates stamping, and date stamping) Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up—up to six columns by six rows maximum for letter/8.5 x 11*/216 x 279 mm/A4 Transparency dividers (blank or printed) Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document—can be used for inserts, tabs, different paper sources, and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher) Stapling (single/dual)
Foreign Device Interface RS-232 Port (optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service PC interface for upload/download of internal auditron data
Accessibility Option	Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.*

_	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems	
ITERNET FAX (optional)		
Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients	
Maximum Scan Area	11.7 x 17"/297 x 432mm/A3	
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell Netware 4.x/5.x/6.x Optional PIN-based guest login	
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)	
File Formats	TIFF-FX profiles S, F, with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression	
Resolutions	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi	
Network Protocols	SMTP POP3 (RFC 1939)	
Compliance	ITU-T T.37 compliant	
	Provides walk-up faxing and hard-copy output of received faxes when integrated with third-party fax-server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number	
	of lines, compatibility and compression are dependent on fax server configuration.	
Fax Send Features		
Fax Send Features  Fax Print Features	of lines, compatibility and compression are dependent on fax server configuration.  One- or two-sided scanning (up to ledger/11 x 17"/279 x 432 mm/A3)  Phone number entry  Add to send list (50 numbers maximum)  Delay send (specific time)  Resolution selection (fine, standard)  Image quality selection (normal, text, halftone photo, photo, background suppression,	
	of lines, compatibility and compression are dependent on fax server configuration.  One- or two-sided scanning (up to ledger/11 x 17"/279 x 432 mm/A3)  Phone number entry  Add to send list (50 numbers maximum)  Delay send (specific time)  Resolution selection (fine, standard)  Image quality selection (normal, text, halftone photo, photo, background suppression, seven levels of contrast, seven levels of sharpness)  One- or two-sided printing (up to ledger/11 x 17"/279 x 432 mm/A3)  Quantity  Staple on/off  Collate on/off  Secure print on/off	

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems
DEVICE MANAGEMENT	
Management Support	SNMP Version 1 and SNMP Version 2c trap MIB access (IETF-MIB II RFC 1213), host resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
CentreWare Network Services	Device Discovery wizard (available at www.xerox.com) Device Administration wizard (available at www.xerox.com) Font management utility
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system.  Works with any SNMP-managed printer from any manufacturer.  Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.  Requires Windows XP or 2000 (Professional or Advanced Server) and Internet Explorer 5.01 or higher.
Novell NDPS/NEPS (gateway for WorkCentre Pro)	Server gateway application: centralized management tool provides streamlined installations via printer agents, automated printer driver installation and downloads, printer and job configuration, configurable event notification.
Xerox CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View.  Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk.
Xerox CentreWare® for Tivoli® NetView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by Tivoli NetView.  Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet.  Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC).
Xerox CentreWare® MC for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server in NT and Windows 2000 environments. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by HP OpenView.  Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons.  Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView.
Xerox Plug and Print 2000	Plug and Print 2000 (PnP2000) is an administrative service program that simplifies enterprise-wide printer installs and relocations for Windows 2000 environments. The product discovers devices, automatically installs devices, enables sharing printers to users and provides install reports—all through a user-friendly interface.
Xerox Barcode Pro PS (optional)	Enables intelligent PostScript barcode printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. This solution enables the printing of barcodes from any application (client or mainframe) that supports PostScript® printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.  Purchase via www.font.net

## WorkCentre® Pro 65/75/90 Advanced Multifunction Systems

#### **DEVICE MANAGEMENT** Continued

Xerox Device Types for SAP R/3 Environment Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL):

- —Simplex or duplex printing
- —Finishing—single or dual stapling
- —Tray pull location from six different trays
- —Print security via PIN ID capability at the WorkCentre Pro

Xerox SAP R/3 PostScript Intelligent Barcode Utility (optional)

Purchase via www.font.net

Provides built-in process intelligence that allows the automated printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox PostScript Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation,

placement of start/stop characters, encoding of data string and data compression.

## PAPER HANDLING—Duplex Automatic Document Feeder (DADF)

Capacity*	100 sheets	
Document Feeder Scan Speed	65 images per minute—letter/8.5 x 11"/216 x 279 mm/A4 long edge feed (LEF)	
Paper Sizes Sensed         Statement/5.5 x 8.5"/140 x 216 mm/A5 LEF or short edge feed (SEF)           Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF           Legal/8.5 x 14"/216 x 356 mm SEF           Ledger/11 x 17"/279 x 432 mm/A3 SEF		
Weights	16 lb to 32 lb bond/60 to 120 gsm	

# PAPER HANDLING—Front-Loading Paper Trays

, a en indialema i	Tolli-Loading Laber Hays	
Number	Four	
Capacity*	500 sheets each	
Sizes	User adjustable from statement/5.5 $\times$ 8.5"/140 $\times$ 216 mm/A5 to ledger/11 $\times$ 17"/279 $\times$ 432 mm/A3 Service adjustable for 12 $\times$ 18"/305 $\times$ 457 mm	
Weights	16 lb bond to 110 lb index/60 to 200 gsm	
Types	Letterhead Preprinted forms Labels Transparencies Hole-punched Recycled paper Bond Index Cover Tab stock Card stock	

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems
PAPER HANDLING—Bypa	ass Tray
Capacity*	50 sheets
Sizes	4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm
Weights	16 lb bond to 110 lb index/60 to 200 gsm
PAPER HANDLING—3,10	00-sheet High-Capacity Feeder (HCF) (WCP 65 optional, 75 standard)
Capacity*	3,100 sheets
Paper Size	Letter/8.5 x 11"/216 x 279 mm/A4 LEF
Weights	16 lb to 32 lb bond/60 to 120 gsm
Total Capacity*	5,150 sheets (with Bypass Tray, Four Trays and High-Capacity Feeder)
PAPER HANDLING—5,10	00-sheet High-Capacity Feeder (HCF) (WCP 75 optional, 90 standard)
Capacity*	5,100 sheets
Paper Size	Letter/8.5 x 11"/216 x 279 mm/A4 LEF
Weights	16 lb to 32 lb bond/60 to 120 gsm
Total Capacity*	7,150 sheets (with Bypass Tray, Four Trays and High-Capacity Feeder)
PAPER HANDLING—11	x 17" Large Capacity Kit (optional with 5,100-sheet HCF)
Capacity* and Paper Sizes	5,100 sheets Letter/8.5 x 11"/216 x 279 mm/A4 LEF 2,500 sheets Ledger/11 x 17"/279 x 432 mm/A3 SEF
Weights	16 lb to 32 lb bond/60 to 120 gsm
PAPER HANDLING—Cor	ovenience Stapler and Work Surface (optional)
Capacity*	Up to 50 sheets 5,000 staples per cartridge

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems
OUTPUT OPTIONS	
Office Finisher (50-sheet stapling)	<b>Top Tray</b> Capacity:* 250 sheets Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm
	Main Tray Capacity:* 2,000 sheets Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm Weights: 16 lb bond to 110 lb index/60 to 200 gsm Stapling Positions: Single and dual, portrait and landscape orientations Maximum Stapler Capacity:* 50 sheets
Advanced Office Finisher (100-sheet stapling)	<b>Top Tray</b> Capacity:* 250 sheets Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm
	Main Tray Capacity:* 2,000 sheets Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm Weights: 16 lb bond to 110 lb index/60 to 200 gsm Stapling Positions: Single and dual, portrait and landscape orientations Maximum Stapler Capacity:* 100 sheets for legal/8.5 x 14"/216 x 356 mm and below; 50 sheets for larger sizes
Professional Finisher	<b>Top Tray</b> Capacity:* 250 sheets Paper Sizes: 4.13 x 5.83"/105 x 148 mm to 12 x 18"/305 x 457 mm
	Main Tray Capacity:* 2,000 sheets Paper Sizes: 7.17 x 10.2"/182 x 257 mm to 12 x 18"/305 x 457 mm Weights: 16 lb bond to 110 lb index/60 to 200 gsm Stapling Positions: Single and dual, portrait and landscape orientations Maximum Stapler Capacity:* 100 sheets for legal/8.5 x 14"/216 x 356 mm and below; 50 sheets for larger sizes
_	Booklet Maker Capacity:* Tray stop up, 30 booklets (one to five sheets per booklet); tray stop down, unlimited Paper Sizes: 8.5 x 11"/216 x 279 mm/A4, 8.5 x 14"/216 x 356 mm, 11 x 17"/279 x 432 mm/A3 Weights: 16 lb bond to 110 lb index/60 to 200 gsm Saddle-Stitch Capacity:* 2 to 15 sheets (8- to 60-page booklet) V-Fold Capacity:* One to five sheets (unstapled)
	Tri-Folder Capacity:* Tray stop up, 55 sheets; tray stop down, unlimited Paper Sizes: 8.5 x 11"/216 x 279 mm/A4 Weights: 16 lb to 24 lb bond/60 to 90 gsm Folding: Single-sheet folds (simplex and duplex), C and Z shapes

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems					
ACCOUNTING						
Accounting With Third-Party Server Applications (optional)	Up-to-the-minute data on how the WorkCentre Pro system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax Multiple accounting vendors, certified by the Xerox Business Partners Program. For details, visit www.xerox.com.					
Internal Auditron	Tracks copy use only; supports up to 2,500 user accounts (1 to 12 digits) or 11,000 general accounts (5 digits)  Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software					
	WorkCentre® Pro 65	WorkCentre® Pro 65 WorkCentre® Pro 75 WorkCentre® Pro 90				
MONTHLY DUTY CYCLE	Duty Cycle: Up to 250,000	Duty Cycle: Up to 300,000	Duty Cycle: Up to 400,000			
BASIC CONFIGURATIONS*						
	Bypass Tray Network Controller Offsetting Catch Tray	3,100-sheet High-Capacity Feeder Office Finisher Network Controller	5,100-sheet High-Capacity Feeder Office Finisher Network Controller			
		WorkCentre® Pro 65/75/90				
ACCESSORIES						
	Office Finisher (50-sheet stapling) Advanced Office Finisher (100-sheet stapling) Professional Finisher (100-sheet stapling, saddle-stitch booklet making, tri-folding) Convenience Stapler 3,100-sheet High-Capacity Feeder (WCP 65 optional, WCP 75 standard) 5,100-sheet High-Capacity Feeder (WCP 75 optional, WCP 90 standard) 11 x 17" Large Capacity Kit (optional with 5,100-sheet HCF) Image Overwrite Security Removable Hard Drive Foreign Device Interface/RS-232 port Copy Pre-collation 128 MB RAM Upgrade Network Scanning With E-Mail Scan to PC Desktop Client Software Network Fax Server Integration Network Accounting Enablement Network Controller RAM Upgrade 128 MB (to 256 MB maximum) USB Printing Port Xerox Copier Assistant Software (assistive software for the visually impaired or persons with limited dexterity or mobility)** Internet Fax SAP R/3 PostScript Intelligent Barcode Utility					

	WorkCentre® Pro Advanced Multifunction				WorkCentre® Pro 90 Advanced Multifunction System		
ELECTRICAL REQUIREMENT	TS .		ı				
	Sole use of 115 volt, 20 ampere, 60 Hz circuit, NEMA 5- 100-sheet Stapling Finisher requires a separate 115 volt 60 Hz circuit, NEMA 5-15R receptacle				Sole use of 120/240 volts (or) 208Y/120-127 Volts, 3-Wire + PE (Protective Earth), 16 ampere, 60Hz, NEMA 14-20R receptacle		
POWER CONSUMPTION							
Running	1,425 watts with 50-sheet Stapling Finisher		1,440 watts with 50-sheet Stapling Finisher		1,870 watts with 50-sheet Stapling Finisher		
	1,865 watts with 100-sheet Stapling Finisher		1,880 watts with 100-sheet Stapling Finisher		2,310 watts with 100-sheet Stapling Finisher		
Standby	450 watts		360 wa	tts	3	341 watts	
Low-Power Mode	255 watts		339 wa	tts	2	80 watts	
Sleep Mode	65 watts		65 watts		59 watts		
Warm-up	Four minutes	our minutes		Four minutes		Three minutes	
Low-Power Recovery	30 seconds (maximum)		30 seconds (maximum)		30 seconds (maximum)		
ENVIRONMENTAL CONSIDER	RATIONS						
Required Temperature Range	50° to 95° F/10° to 35° C		50° to 95° F/10° to 35° C		50° to 95° F/10° to 35° C		
Required Relative Humidity	10% to 90%		10% to 90%		10% to 90%		
Noise Emission	39.4 dBA standby; 63.2 dBA operating; 73.3 dBA impulse		39.4 dBA standby; 62.9 dBA operating; 69.0 dBA impulse		38.5 dBA standby; 64.2 dBA operating; 70.6 dBA impulse		
Heat Emission	1,540 BTU/hr standby; 4,870 BTU/hr operatin	3 .		) BTU/hr standby; 5 BTU/hr operating		1,165 BTU/hr standby; 6,356 BTU/hr operating	
Ozone Emission < 0.01 parts per million		1	< 0.01 parts per million		< 0.01 parts per million		
	WorkCentre® Pro 65/75/90						
DIMENSIONS AND WEIGHT							
	Width	Depti	h	Height		Weight	
Fully Configured With 50-Sheet Stapling Office Finisher	69"/1,753 mm	28"/7	10 mm	44.8"/1,138 mm		538 lbs/245 kg	
Fully Configured With 100-Sheet Stapling Advanced Office Finisher	80"/2,032 mm	28"/710 mm		44.8"/1,138 mm		609 lbs/278 kg	
Fully Configured With Professional Finisher	88"/2,235 mm	28"/710 mm		44.8"/1,138 mm		686 lbs/312 kg	

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems			
SPACE REQUIREMENTS*				
	Width	Depth	Height	
Fully Configured With 50-Sheet Stapling Office Finisher	102"/2,591 mm	69"/1,753 mm	78"/1,981 mm	
Fully Configured With 100-Sheet Stapling Advanced Office Finisher	107"/2,718 mm	69"/1,753 mm	78"/1,981 mm	
Fully Configured With Professional Finisher	109"/2,769 mm	69"/1,753 mm	78"/1,981 mm	

# **CERTIFICATIONS**

FCC Class B Compliant (U.S.), DOC Class B Compliant (Canada)

89/336/EEC (Europe)

UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950)

73/23/EEC (Europe) 95/5/EEC (Europe) WHQL, Novell NetWare

SUPPLIES					
	Description	Order Number	No. per Box	Expected Yield	
	Dry Ink Cartridge	6R1006	6	23,500 (65); 24,500 (75); 28,000 (90) per cartridge at 6% area coverage	
	Convenience Stapler Staple Cartridge	108R53	3	5,000 staples per cartridge	
_	Staple Cartridge (for Office [50-sheet stapling] Finisher)	108R53	3	5,000 staples per cartridge	
	Staple Housing Cartridge (for Advanced Office [100-sheet stapling] Finisher and Professional Finisher)	8R12912	1	N/A	
	Note: Staple Housing Cartridge comes filled with 5,000 staples.				

	WorkCentre® Pro 65/75/90 Advanced Multifunction Systems				
<b>SUPPLIES</b> Continued					
	Description	Order Number	No. per Box	Expected Yield	
	Staples for Staple Housing Cartridge (for Advanced Office [100-sheet stapling] Finisher and Professional Finisher)	8R12898	3	5,000 staples per cartridge	
	Professional Finisher Booklet Maker Staples	8R12897	8	2,000 staples per cartridge	

# Total satisfaction guaranteed.

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox WorkCentre® Pro which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.









© 2004 Xerox Corporation. All rights reserved. XEROX\*, CentreWare\*, WorkCentre\* Pro and Copier Assistant are trademarks of Xerox Corporation. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox corporation are neconstant are reconditioned. ENERGY STAR\* is a U.S. registered mark. As an ENERGY STAR\* Partner, Xerox Corporation has determined that these products meet the ENERGY STAR\* guidelines for energy efficiency. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product appearance, build status and/or specifications are subject to change without notice. 3/04, 6/04, 02/05

10 P65FS-01UE

10 P65FS-01UE

10 P65FS-01UE

11 P65FS-01UE